DS-LEDUNV Models










- Contact a Peerless-AV® Sales Representative for the current list of compatible latching dvLED display models
- 1:1 and preconfigured models ensure the right solution is available to meet your needs
- Condensed packaging reduces environmental impact, shipping costs, and warehouse space when storing
- Open architecture provides ease of cable management
- Optional Trim Kit Accessory is compatible with most displays (DS-LEDTK Models)
- Maximum Size: Up to 32'W x 9'H (Configuration based on display size) Configurations that exceed 50% of the limit will require onsite installation consultation

SEAMLESS KITTED UNIVERSAL

dvLED Mounting System

The Peerless-AV® SEAMLESS Kitted Universal dvLED Mounting System features a slim and versatile design. This cost-effective, kitted solution is enabled by a patent-pending universal spacer that makes it adaptable for most latching dvLED displays. The display adaptors and mount frame provide X, Y and Z axis adjustments to overcome uneven walls and to ensure the video wall remains flat. The lightweight aluminum frame quickly mounts to the wall and the quick-connect clamps allow installers to easily secure the displays to the mount frame. Compact packaging reduces warehouse space and generally allows for parcel shipping, which lowers the overall delivery costs. Quickly and easily build the perfect dvLED video wall for a corporate lobby, retail display, sportsbook, concert hall, casino, and much more with Peerless-AV's SEAMLESS Kitted Universal dvLED Mounting System.



*Universal spacer (DS-LEDUNVSPACER) is included with the preconfigured models only, sold separately with the 1:1 models.



SEAMLESS by Peerless-AV® - dvLED Video Wall Integration Program offers:



EXPERT ENGINEERING & DESIGN




CUSTOM PROJECT MANAGERS



FULL INSTALLATION SERVICES



SEAMLESS dvLED MOUNTING SYSTEMS





peerless-av.com/SEAMLESS

DS-LEDUNV Models

SEAMLESS Kitted Universal dvLED Mounting System

Product Specifications

| | DIMENSIONS (W x H x D) | DDODUCT WEIGHT | LOAD CADACITY | EINIICH | AVAILABLE COLORS | | | |
|--|---|---|------------------------------|--|--------------------------------------|--|--|--|
| 1:1 MODELS | DIMENSIONS (W X H X D) | PRODUCT WEIGHT | LOAD CAPACITY | FINISH | AVAILABLE COLORS | | | |
| DS-LEDUNV610 DS-LEDUNV960 DS-LEDUNV1220 | 24" x 3.2" x 2.74"-3.49" (610 x 81 x 70-89mm) 37.8" x 3.2" x 2.74"-3.49" (960 x 81 x 70-89mm) 48" x 3.2" x 2.74"-3.49" (1220 x 81 x 70-89mm) | 2.8lb (1.3kg) 3.2lb (1.5kg) 3.8lb (1.7kg) | 52lb (23.6kg) per display | Powder Coat and Clear Anodized Finish | Black Brackets, Silver Extrusions | | | |
| DS-LEDUNVSPACER | 46.7" x 4.1" x 3.2" (1187 x 104 x 81mm) | 14.4lb (6.5kg) | NA | Powder Coat | Black | | | |
| PRECONFIGURED MODELS Product height is dependent on the display height. | | | | | | | | |
| DS-LEDUNV610-4x4 DS-LEDUNV610-5x5 DS-LEDUNV610-6x6 DS-LEDUNV610-8x8 | 96" x VARIES x 2.74"-3.49" (2,438 x VARIES x 70-89mm) 120" x VARIES x 2.74"-3.49" (3,048 x VARIES x 70-89mm) 144" x VARIES x 2.74"-3.49" (3,658 x VARIES x 70-89mm) 192" x VARIES x 2.74"-3.49" (4,877 x VARIES x 70-89mm) | 33lb (15.1kg) 59lb (26.8kg) 75lb (34.0kg) 133lb (60.7kg) | | Powder Coat and Clear Anodized Finish | Black Brackets, Silver Extrusions | | | |
| DS-LEDUNV960-3x3 DS-LEDUNV960-4x4 DS-LEDUNV960-5x5 | 113.4" x VARIES x 2.74"-3.49" (2,880 x VARIES x 70-89mm) 151.2" x VARIES x 2.74"-3.49" (3,840 x VARIES x 70-89mm) 189" x VARIES x 2.74"-3.49" (4,800 x VARIES x 70-89mm) | 31lb (14.1kg) 55lb (24.8kg) 72lb (32.8kg) | 52lb (23.6kg) per display | | | | | |
| DS-LEDUNV1220-2x2 DS-LEDUNV1220-3x3 DS-LEDUNV1220-4x4 | 96" x VARIES x 2.74"-3.49" (2,438 x VARIES x 70-89mm) 144" x VARIES x 2.74"-3.49" (3,658 x VARIES x 70-89mm) 192" x VARIES x 2.74"-3.49" (4,877 x VARIES x 70-89mm) | 14lb (6.3kg) 31lb (14.2kg) 55lb (24.8kg) | | | | | | |

Package Specifications

| Package Specifications | | | | | | | | | | |
|---|---|---|--|---|------------------|--|--|--|--|--|
| 1:1 MODELS | PACKAGE SIZE (W x H x D) | PACKAGE SHIP WEIGHT | PACKAGE UPC CODE | PACKAGE CONTENTS | UNITS IN PACKAGE | | | | | |
| DS-LEDUNV610 DS-LEDUNV960 DS-LEDUNV1220 | 25.3" x 4.5" x 3.1" (641 x 114 x 79mm) 38.6" x 4.4" 4.4" (981 x 111 x 111mm) 48.6" x 4.4" x 4.4" (1235 x 111 x 111mm) | 3.5lb (1.6kg) 4.0lb (1.8kg) 5lb (6.9kg) | 735029355779 735029355823 735029355731 | Wall Plate, Extrusion, Connector Plate, Quick-Connect Adaptor Clamps, Standoff and Mounting Hardware | 1 | | | | | |
| DS-LEDUNVSPACER | 28.3" x 5" x 4.3" (718 x 127 x 108mm) | 15.3lb (6.9kg) | 735029355724 | Universal Spacer, Shims and Wrench | | | | | | |
| PRECONFIGURED MODELS *Universal spacer (DS-LEDUNVSPACER) is included with the preconfigured models only, sold separately with the 1:1 models. | | | | | | | | | | |
| DS-LEDUNV610-4x4 DS-LEDUNV610-5x5 DS-LEDUNV610-6x6 DS-LEDUNV610-8x8 DS-LEDUNV960-3x3 DS-LEDUNV960-4x4 DS-LEDUNV960-5x5 | 49.5" x 14.3" x 9.0" (1257 x 362 x 229mm) 49.5" x 14.3" x 9.0" (1257 x 362 x 229mm) 49.5" x 14.3" x 9.0" (1257 x 362 x 229mm) 49.5" x 14.3" x 13.0" (1257 x 362 x 239mm) 49.5" x 14.3" x 9.0" (1257 x 362 x 229mm) 49.5" x 14.3" x 9.0" (1257 x 362 x 229mm) 49.5" x 14.3" x 9.0" (1257 x 362 x 229mm) 49.5" x 14.3" x 9.0" (1257 x 362 x 229mm) | 56lb (25.6kg) 83lb (37.8kg) 100lb (45.6kg) 165lb (74.8kg) 54lb (24.5kg) 78lb (35.3kg) 96lb (43.8kg) | 735029355786 735029355793 735029355809 735029355816 735029355830 735029355847 735029355854 | Universal Spacer, Wall Plate, Extrusion, Connector Plate, Quick-Connect Adaptor Clamps, Standoff and Mounting Hardware | 1 | | | | | |
| DS-LEDUNV1220-2x2 DS-LEDUNV1220-3x3 DS-LEDUNV1220-4x4 | 49.5" x 14.3" x 9.0" (1257 x 362 x 229mm) 49.5" x 14.3" x 9.0" (1257 x 362 x 229mm) 49.5" x 14.3" x 9.0" (1257 x 362 x 229mm) | 36lb (16.2kg) 54lb (24.6kg) 78lb (35.3kg) | 735029356059 735029356066 735029356073 | | | | | | | |

Accessories DS-LEDTK Models: Universal Trim Kit for dvLED Video Walls 3.9" to 6.3" (99-160mm) Deep

Components:

ALUMINUM EXTRUSION CUT TO LENGTH BY INSTALLER PATENT-PENDING UNIVERSAL SPACER Included with preconfigured models only,

2.74" 3.49" (70mm) (89mm) MIN. MAX.

SIDE VIEW WITH dvLED DISPLAY

Architect Specifications

The SEAMLESS Kitted Universal dvLED Mounting System shall be a Peerless-AV DS-LEDUNV and shall be located where indicated on the plans. Assembly and installation shall be done according to instructions provided by the manufacturer.

sold separately with 1:1 models

Visit **peerless-av.com** to see the complete line of AV solutions from Peerless-AV, including outdoor displays, kiosks, display mounts, projector mounts, carts/stands, and a full assortment of accessories. Peerless-AV 2300 White Oak Circle Aurora, IL 60502

(800) 865-2112 (630) 375-5100 Peerless-AV EMEA Unit 2 Curo Park

Frogmore, St. Albans Hertfordshire, AL2 2DD United Kingdom

+44 (0) 1923 200 100

Peerless-AV B.V. Papendorpseweg 75 3528 BJ Utrecht The Netherlands

+31 (0) 70 770 8037

Peerless-AV Latin America Av. de las Industrias 413 Parque Industrial Escobedo General Escobedo, N.L., México, 66062

+52 (81) 8384-8300



All dimensions = inch (mm)