

NOVACOLOR DESIGN

Pigments in liquid form

- ▷ **Water based**
- ▷ **Suitable for internal and external areas**
- ▷ **Resistant to UV radiation**
- ▷ **Excellent alkaline strength**

Description

NOVACOLOR DESIGN are water-based pigments with high color and weathering fastness. Suitable for mixing with the micro-cement PLANOCOLOR PREMIUM 2K & SP as well as NOVACEM MICRO TERRAZZO cement screeds. Complies with Directive 2004/42/ EC for special two component renders for specific uses (subcategory I, type Y) with a maximum VOC content of less than 140 g/L. The VOC content is less than 0.3 g/L. APEO free.

Technical Data

Product Identification

Consistency	Liquid
Color	Depending on the packaging indication
Color shades	Standardized color chart RAL 1002, 1013, 1014, 1015, 1019, 1021, 1024, 2009, 3004, 3012, 3015, 3020, 4006, 4009, 5012, 5024, 6001, 6013, 6019, 7000, 7001, 7002, 7004, 7005, 7006, 7011, 7012, 7013, 7016, 7022, 7023, 7030, 7031, 7032, 7035, 7036, 7038, 7039, 7040, 7042, 7044, 7047, 8001, 8017, 8019, 9001, 9002, 9003, 9010, 9017 9018; 9003+10% Non standardized color chart 0032, 0035, 0014, 0024, 0034, 0044, 0054, 0064, 0074, 0084

Application Procedure

Application	Before using, shake the container well. Add the correct quantity depending the mortar in order to achieve the desired shade of the PLANOCOLOR color chart.
Relative products	Also available as NOVACOLOR DESIGN A/V version for the micro-cement PLANOCOLOR ANTICO & PLANOCOLOR VENETICO to achieve the shades of the PLANOCOLOR color chart.
Recommendations	• Do not exceed the recommended dosages for the mortars • It is recommended to completely empty the container to reach the color shade • It is recommended that the application be made by a professional user
Consumption	According to the instructions of PLANOCOLOR systems.
Storage	NOVACOLOR DESIGN remains stable for at least 12 months from the production date in the original sealed packaging stored in a dry place and temperature between +5°C and +35°C.
Packaging	Plastic bottles 250 or 500ml.
Safety Instructions	For information and instructions regarding disposal and safe handling, users should refer to the latest Safety Data Sheet of the product containing ecological, toxicological and other safety related data.
Legal Notes	The technical data and recommendations contained or listed in this leaflet are the result of laboratory measurements, of our current knowledge and experience. All the above-mentioned information and specifications should in any case be considered as indicative, as they may differ from each other. The Company makes every effort to ensure the accuracy of the information provided herein. Product specifications, prices and availability are subject to change without notice and may differ from those shown. In practice, variations in materials, substrates and on-site implementation conditions are such that no warranty can be given or implied, as to the merchantability or suitability of the materials for a particular purpose and for the exact conditions of each project. Anyone interested of using the product must be sure beforehand that the product is suitable for the intended use and in any case, the user is solely responsible for any consequences due to the use of the product. Among other things, the Company is not responsible for any normal wear or tear from environmental or other inappropriate conditions. We reserve the right to revise or change the data herein without prior notice. Restrictions and disclaimers apply to the extent permitted by applicable law. The Company has a Technical Support Department, which is the only one responsible for providing technical advice and solutions to deal with problems. Requests to the Technical Support Department are addressed and answered, only in writing.

For the latest and a valid version of the Technical Data Sheet, the user of the material must refer to our website www.novamix.gr or directly to the QR Code of the product.



DOMOCHEMICAL S.A.
40 Papanikoli str.
Chalandri, 15232, Athens
T +30 210 68 93 953
F +30 210 68 94 571
novamix@novamix.gr