



Lytespan® Track Lighting System **8237WH**


PAR-Tech™ Bezel 30 Shade
8237WH
8237BK



BEZEL 30 WITH LOW PROFILE ADAPTER



BEZEL 30 WITH HINGED ADAPTER



Ordering Information

Catalog No.	Finishes	Mounting	Lamps
8237WH 8237BK	Matte White Matte Black	All Lytespan Track Systems	PAR30, 75W Max. (Tungsten-Halogen)

Features

- Shade Attachment:** Zinc plated and painted C.R. steel. Bayonet fitting.
- Shade:** Single piece die-cast aluminum.
- Front Bezel:** High temperature ULTEM® integral color. Shields extraneous spill light.
- Shade Rear Vents:** Aligns with Adapter's vents for effective air circulation.
- Color Accent Ring:** Silicone rubber.

Finish

All painted finishes baked enamel.

Options & Accessories

3 1/2" Beam Smoother, Beam Elongator, Louver and Barn Doors.
All require Accessory Holder 8593.
See Lightolier Specification Sheets AL3HC, AF3LF, AF3AS.

Labels


UL; I.B.E.W.

Ultem® is a trademark of General Electric.

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

Lightolier a Genlyte company
631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
We reserve the right to change details of design, materials and finish.
© 2007 Genlyte Group LLC • B0607

LIGHTOLIER®



Lytespan® Track Lighting System **8237WH**

Page 2 of 2


PAR-Tech™ Bezel 30 Shade

Lighting Data Aiming Angle


L Beam Length
W Beam Width
C Distance to center beam
D Distance
A Aiming Angle
FC Footcandles

L and **W** are the outer points where the candle power drops to 50% of the maximum. **FC** are the initial footcandles at the center of the beam.


0°



30°, 45° or 60° Horizontal



30°, 45° or 60° Vertical



LAMP

	Beam Spread 50% Max. CP	Beam Center C.P. Candelas	Rated Life-Hrs
 50W PAR30 NSP (Halogen)	8Y	9,200	2,000
 50W PAR30 NSP (Halogen-IR)	8Y	17,000	3,000
 50W PAR30 NFL (Halogen)	25Y	2,000	2,000
 50W PAR30 NFL (Halogen-IR)	25Y	3,000	3,000
 50W PAR30 FL (Halogen)	35Y	1,400	2,500
 50W PAR30 FL (Halogen-IR)	37Y	1,600	3,000
 75W PAR30 NSP (Halogen)	9Y	14,000	2,500
 75W PAR30 NFL (Halogen)	30Y	3,200	2,500
 75W PAR30 FL (Halogen)	40Y	2,000	2,500

0° AIMING ANGLE

D	FC	L	W
7'	188	1.0'	1.0'
10'	92	1.4'	1.4'
13'	54	1.8'	1.8'
16'	36	2.2'	2.2'
8'	266	1.1'	1.1'
12'	118	1.7'	1.7'
16'	66	2.2'	2.2'
20'	43	2.8'	2.8'
4'	125	1.8'	1.8'
6'	58	2.7'	2.7'
8'	31	3.5'	3.5'
10'	20	4.4'	4.4'
6'	83	2.7'	2.7'
8'	47	3.5'	3.5'
10'	30	4.4'	4.4'
12'	21	5.3'	5.3'
3'	158	1.9'	1.9'
5'	56	3.2'	3.2'
7'	29	4.4'	4.4'
9'	17	5.7'	5.7'
3'	178	2.0'	2.0'
5'	64	3.3'	3.3'
7'	33	4.7'	4.7'
9'	20	6.0'	6.0'
8'	219	1.3'	1.3'
12'	97	1.9'	1.9'
16'	55	2.5'	2.5'
20'	35	3.1'	3.1'
6'	89	3.2'	3.2'
8'	50	4.3'	4.3'
10'	32	5.4'	5.4'
12'	22	6.4'	6.4'
4'	125	2.9'	2.9'
6'	56	4.4'	4.4'
8'	31	5.8'	5.8'
10'	20	7.3'	7.3'

A=30° AIMING ANGLE

D	C	FC	L	W
6'	3.5'	166	1.1'	1.0'
9'	5.2'	74	1.7'	1.5'
12'	6.9'	41	2.2'	1.9'
15'	8.7'	27	2.8'	2.4'
7'	4.0'	225	1.3'	1.1'
10'	5.8'	110	1.9'	1.6'
13'	7.5'	65	2.4'	2.1'
16'	9.2'	43	3.0'	2.6'
3'	1.7'	144	1.8'	1.5'
5'	2.9'	52	3.0'	2.6'
7'	4.0'	27	4.2'	3.6'
9'	5.2'	16	5.4'	4.5'
5'	2.9'	78	3.0'	2.6'
7'	4.0'	40	4.2'	3.6'
9'	5.2'	24	5.4'	4.6'
11'	6.4'	16	6.6'	5.6'
3'	1.7'	101	2.6'	2.2'
5'	2.9'	36	4.3'	3.6'
7'	4.0'	19	6.1'	5.1'
9'	5.2'	11	7.8'	6.6'
3'	1.7'	115	2.8'	2.3'
5'	2.9'	42	4.6'	3.9'
7'	4.0'	21	6.5'	5.4'
9'	5.2'	13	8.3'	7.0'
7'	4.0'	186	1.5'	1.3'
10'	5.8'	91	2.1'	1.8'
13'	7.5'	54	2.7'	2.4'
16'	9.2'	36	3.4'	2.9'
5'	2.9'	83	3.7'	3.1'
7'	4.0'	42	5.1'	4.3'
9'	5.2'	26	6.6'	5.6'
11'	6.4'	17	8.1'	6.8'
3'	1.7'	144	3.0'	2.5'
5'	2.9'	52	5.1'	4.2'
7'	4.0'	27	7.1'	5.9'
9'	5.2'	16	9.1'	7.6'

A=45° AIMING ANGLE

D	C	FC	L	W
4'	4.0'	203	1.1'	0.8'
6'	6.0'	90	1.7'	1.2'
8'	8.0'	51	2.2'	1.6'
10'	10.0'	33	2.8'	2.0'
5'	5.0'	240	1.4'	1.0'
7'	7.0'	123	2.0'	1.4'
9'	9.0'	74	2.5'	1.8'
11'	11.0'	50	3.1'	2.2'
3'	3.0'	79	2.8'	1.9'
4'	4.0'	44	3.7'	2.5'
5'	5.0'	28	4.7'	3.1'
6'	6.0'	20	5.6'	3.8'
3'	3.0'	118	2.8'	1.9'
5'	5.0'	42	4.7'	3.1'
7'	7.0'	22	6.5'	4.4'
9'	9.0'	12	8.4'	5.6'
2'	2.0'	124	2.8'	1.8'
3'	3.0'	55	4.2'	2.7'
4'	4.0'	31	5.6'	3.8'
5'	5.0'	20	7.0'	4.5'
2'	2.0'	141	3.0'	1.9'
3'	3.0'	63	4.5'	2.8'
4'	4.0'	35	6.0'	3.8'
5'	5.0'	23	7.5'	4.7'
5'	5.0'	198	1.6'	1.1'
7'	7.0'	101	2.2'	1.6'
9'	9.0'	61	2.9'	2.0'
11'	11.0'	41	3.5'	2.4'
3'	3.0'	126	3.5'	2.3'
5'	5.0'	45	5.8'	3.8'
7'	7.0'	23	8.1'	5.3'
9'	9.0'	14	10.4'	6.8'
3'	3.0'	79	5.0'	3.1'
4'	4.0'	44	6.7'	4.1'
5'	5.0'	28	8.4'	5.1'
6'	6.0'	20	10.1'	6.1'

A=60° AIMING ANGLE

D	C	FC	L	W
2'	3.5'	288	1.1'	0.6'
3'	5.2'	128	1.7'	0.8'
4'	6.9'	72	2.3'	1.1'
5'	8.7'	46	2.8'	1.4'
3'	5.2'	236	1.7'	0.8'
4'	6.9'	133	2.3'	1.1'
5'	8.7'	85	2.8'	1.4'
6'	10.4'	59	3.4'	1.7'
1'	1.7'	250	2.1'	0.9'
2'	3.5'	63	4.2'	1.8'
3'	5.2'	28	6.2'	2.7'
4'	6.9'	16	8.3'	3.5'
2'	3.5'	94	4.2'	1.8'
3'	5.2'	42	6.2'	2.7'
4'	6.9'	23	8.3'	3.5'
5'	8.7'	15	10.4'	4.4'
1'	1.7'	175	3.6'	1.3'
2'	3.5'	44	7.2'	2.5'
3'	5.2'	19	10.8'	3.8'
4'	6.9'	11	14.4'	5.0'
1'	1.7	200	4.0'	1.3'
2'	3.5'	50	8.1'	2.7'
3'	5.2'	22	12.1'	4.0'
4'	6.9'	13	18.1'	5.4'
3'	5.2'	184	1.9'	0.9'
4'	6.8'	109	2.6'	1.3'
5'	8.7'	70	3.2'	1.6'
6'	10.4'	49	3.8'	1.9'
2'	3.5'	100	5.5'	2.1'
3'	5.2'	44	8.2'	3.2'
4'	6.9'	25	10.9'	4.3'
5'	8.7'	16	13.7'	5.4'
1'	1.7'	250	4.8'	1.5'
2'	3.5'	63	9.7'	2.9'
3'	5.2'	28	14.5'	4.4'
4'	6.9'	16	19.3'	5.8'

Job Information

Type:

Lightolier a Genlyte company

www.lightolier.com

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710

We reserve the right to change details of design, materials and finish.

© 2007 Genlyte Group LLC • B0607

LIGHTOLIER