

PLANOCOLOR GRANULATES LC

Colored synthetic granulates

- ▷ **Array of colors**
 - ▷ **Polygonal geometry**
 - ▷ **Resistant to UV radiation and corrosive chemicals**
 - ▷ **Stable granulometric gradation**
-

Description

PLANOCOLOR GRANULATES LC are synthetic colored aggregates of high quality. They are of low specific weight, polygonal, clean and of stable granulometry. Suitable for finishing systems with transparent resins such as PLANOCOLOR AC, PU and LIQUID GLASS as well as with the specialized hydraulic binders NOVACEM CREATIVE and NOVACEM CREATIVE FLOOR for the creation of pebble and mosaic floors and structures still resistant to waterproofing and highly corrosive substances.

Technical Data

Product Identity

Chemical composition	Polyester resin UV stabilized
----------------------	-------------------------------

Specific weight	1.1 kg/L
-----------------	----------

Color	Granulometry
-------	--------------

- Yellow
- Red
- Green
- Dark Blue
- Turquoise
- Brown
- Gold

Code 60: 1.0 – 3.0 mm, special granulometries on request

Application Procedure

Application

Depending on the type of binder. For more information refer to the Technical Data Sheets of PLANOCOLOR AC, PU and LIQUID GLASS Products as well as NOVACEM CREATIVE & NOVACEM CREATIVE FLOOR.

Packaging

Buckets of 5kg.

Safety Instructions

For information and instructions regarding disposal and safe handling, users should refer to the latest Safety Data Sheet of the product containing ecological, toxicological and other safety related data.

Legal Notes

The technical data and recommendations contained or listed in this leaflet are the result of laboratory measurements, of our current knowledge and experience. All the above-mentioned information and specifications should in any case be considered as indicative, as they may differ from each other. The Company makes every effort to ensure the accuracy of the information provided herein. Product specifications, prices and availability are subject to change without notice and may differ from those shown.

In practice, variations in materials, substrates and on-site implementation conditions are such that no warranty can be given or implied, as to the merchantability or suitability of the materials for a particular purpose and for the exact conditions of each project. Anyone interested of using the product must be sure beforehand that the product is suitable for the intended use and in any case, the user is solely responsible for any consequences due to the use of the product. Among other things, the Company is not responsible for any normal wear or tear from environmental or other inappropriate conditions. We reserve the right to revise or change the data herein without prior notice.

Restrictions and disclaimers apply to the extent permitted by applicable law. The Company has a Technical Support Department, which is the only one responsible for providing technical advice and solutions to deal with problems. Requests to the Technical Support Department are addressed and answered, only in writing.

For the latest and a valid version of the Technical Data Sheet, the user of the material must refer to our website www.novamix.gr or directly to the QR Code of the product.



DOMOCHEMICAL S.A.
40 Papanikoli str.
Chalandri, 15232, Athens
T +30 210 68 93 953
F +30 210 68 94 571
novamix@novamix.gr